

Xen Shell - Feature # 133: Use local apt-cacher for Debian/Ubuntu installs

Status:	Resolved	Priority:	Normal
Author:	admin	Category:	
Created:	2016-02-27	Assigned to:	
Updated:	2016-02-27	Due date:	
Subject:	Use local apt-cacher for Debian/Ubuntu installs		
Description:	Debian/Ubuntu installs currently use a well-known remote mirror, but there is no reason why they shouldn't use the local apt-cacher which aside from probably being faster would also avoid chargeable data transfer.		

History

2016-02-27 05:48 - admin

- Status changed from New to Resolved

Installer does actually use apt-cacher. In preseed file:

```
<pre>
# Force use of our own apt-cache
d-i mirror/country          string    manual
d-i mirror/protocol         string    http
d-i mirror/http/hostname    string    apt-cacher.lon.bitfolk.com
d-i mirror/http/directory   string    /debian/ftp.uk.debian.org/debian
</pre>
```

It's only the initial kernel and initramfs that are downloaded from an external mirror.

These could possibly be hosted locally also, but:

- * This would be more complicated as apt-cacher only caches an apt repository and the installer files aren't in an apt repository.
- * They're only a couple of megabytes in size anyway.

So I'm not convinced it's worth the hassle to do that.